



# NTN BEARING CORP.OF

## 130 mm x 200 mm x 33 mm NTN 7026 Angular Contact Ball Bearings



Bearing No. 7026

7026 Bearing 2D drawings and 3D CAD models

Size	130x200x33 mm
Bore Diameter	130 mm
Outer Diameter	200 mm
Width	33 mm
d	130 mm
D	200 mm
B	33 mm
C	33 mm
Angle ( ° )	25 °
a	64 mm
r min.	2 mm
r1 min.	1 mm
da min.	140 mm
ra max.	2 mm
Weight	3,73 Kg
Basic dynamic load rating (C)	117 kN
Basic static load rating (C0)	125 kN
(Grease) Lubrication Speed	3 300 r/min
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	3.57
Product Group	B00308



## NTN BEARING CORP.OF

Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	30 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 30 Degree; 1 (Single)
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Width	1.299 Inch   33 Millimeter
Outside Diameter	7.874 Inch   200 Millimeter
Bore	5.118 Inch   130 Millimeter
bore diameter:	130 mm
radial static load capacity:	125000 N
outside diameter:	200 mm



## NTN BEARING CORP.OF

operating temperature range:	-40 to 120 ° C
overall width:	33 mm
cage material:	Brass
contact angle:	30 °
maximum rpm:	4400 rpm
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 0
closure type:	Open
fillet radius:	2 mm
snap ring included:	Without Snap Ring
weight:	3.570 kg
bearing material:	High Carbon Chrome Steel
manufacturer product page:	<a href="#">Click here</a>
radial dynamic load capacity:	117000 N